



# P & S Sales, Inc.

## Material Safety Data Sheet

Date Issued: 8/16/2011

Product Name:

**C10 - Hi Tone Glaze**

### 1. Product and Company Information

P & S Sales, Inc  
20943 Cabot Blvd.  
Hayward CA 94545

Emergency Number: 800-255-3924  
Customer Service: 510-732-2628  
Business Fax: 510-732-2632

Generic Description: Thin amber color, cloudy liquid with aromatic solvent odor

NFPA Profile: Health 1 Flammability 2 Reactivity 0

### 2. OSHA Hazard Components

CAS Number	Wt %	Component Name
64742-95-6	5%	Solvent Naphtha, Light Aromatic
8052-41-3	7%	Aliphatic Mineral Spirits
68551-19-9	15%	C12-C14 Isoalkanes
617-53-2		Diatomaceous Earth

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

### 3. Effects of Overexposure

#### Acute Exposure

Inhalation: High vapor concentrations (greater than approximately 1000 ppm are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

Contact: Petroleum Solvents/Petroleum Hydrocarbons - Skin contact may aggravate an existing dermatitis.

### 4. First Aid Measures

#### EYE CONTACT

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

#### SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

#### INHALATION

If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

#### INGESTION

If ingested, DO NOT induce vomiting; call a physician immediately.

### 5. Fire Fighting Measures

Flash Point	42°C (107°F) TCC	Upper Flamability Limit	12.6 %
Auto Ignition		Lower Flamability Limit	



# P & S Sales, Inc.

## Material Safety Data Sheet

Date Issued: 8/16/2011

Product Name:

**C10 - Hi Tone Glaze**

**Auto Ignition** 471°C (880°F)

**Lower Flammability Limit** 1.9 %

### FLAMMABLE OR EXPLOSIVE LIMITS (APPROXIMATE PERCENT BY VOLUME IN AIR)

Estimated values: Lower Flammable Limit 1.9% Upper Flammable Limit 12.6%

### EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

### DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

## 6. Accidental Release Measures

### CLEAN WATER ACT / OIL POLLUTION ACT

This product may be classified as an oil under Section 311 of the Clean Water Act, and under the Oil Pollution Act. Discharges or spills into or leading to surface waters that cause a sheen must be reported to the National Response Center (1-800-424-8802).

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

## 7. Handling and Storage

### HANDLING PRECAUTIONS

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Keep product away from ignition sources, such as heat, sparks, pilot lights, static electricity, and open flames.

## 8. Exposure Controls and Personal Protection

64742-95-6 Solvent Naphtha, Light Aromatic  
8052-41-3 Aliphatic Mineral Spirits  
68551-19-9 C12-C14 Isnalkanes

25 ppm STEL  
100 ppm ACGIH (TLV)  
none established





# P & S Sales, Inc.

## Material Safety Data Sheet

Date Issued: 8/16/2011

Product Name:

**C10 - Hi Tone Glaze**

Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA).

### 13. Disposal Information

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.

### 14. Transportation Information

Domestic Ground Shipments in combination packaging under 1.3 Gallons interior package  
This product is not considered a flammable hazard excepted 173.150(b)(3)

International Shipments, Transported by air or marine vessel, Single or combination Packages over 1.3 Gallons  
UN1993, Flammable Liquid n.o.s. (Naphtha Solvent), 8, PGIII

### 15. Regulatory Information

THRESHOLD PLANNING QUANTITY (TPQ), EPA REGULATION 40 CFR 355  
(SARA Sections 301-304)

No TPQ for product or any constituent greater than 1% or 0.1% (carcinogen).

TOXIC CHEMICAL RELEASE REPORTING, EPA REGULATION 40 CFR 372 (SARA Section 313)

This product contains approximately 1.8% 1,2,4-trimethyl benzene.

HAZARDOUS CHEMICAL REPORTING, EPA REGULATION 40 CFR 370 (SARA Sections 311-312)

EPA Hazard Classification Codes: Chronic, Fire

TOXIC SUBSTANCES CONTROL ACT (TSCA)

This product does not contain polychlorinated biphenyls (PCB's).

All components of this product are listed on the U.S. TSCA inventory.

### 16. Other Information

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.



# P & S Sales, Inc.

Material Safety Data Sheet

Product Name:

Date Issued: 8/16/2011

**C10 - Hi Tone Glaze**

---