

COMPLIANT CAR CARE - MATERIAL SAFETY DATA SHEET

SUPER VISION GLASS CLEANER

SECTION I COMPANY INFORMATION		EMERGENCY TELEPHONE NUMBER 1-(800) 255-3924
PRODUCT NAME:	Super Vision Glass Cleaner	
MFG. FOR:	Compliant Car Care Products Division	
ADDRESS:	20943 Cabot Blvd. Hayward, CA 94545	
BUSINESS PHONE:	510-732-2628	
DATE PREPARED:	3/1/99	

SECTION II HAZARDOUS COMPONENTS				
Component Name	CAS #	PEL (OSHA)	ACGIH TLV	Other Limits Recommended
Isopropanol	67-63-0	400 ppm	400 ppm	500 STEL
Butyl Cellosolve	111-76-2	50 ppm (skin)		
* This chemical is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372.				

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS				
Boiling Point	212°F	Specific Gravity (H ₂ O=)	0.97	
Vapor Pressure	18 mmHg	Melting Point	n/a	
Vapor Density (Air=)	1.1	Evaporation rate	0.40	
Solubility in Water	Soluble	pH	6.5	
Appearance/Odor	Green/Clear Liquid/Alcohol odor			

SECTION IV FIRE AND EXPLOSION HAZARD DATA				
Flash Point(Method)	250 F	Flammable Limits	LEL=2.00%	UEL=12.00%
Extinguishing Media	Foam=no	CO ₂ =yes	Water Spray=no	Dry Chemical=yes
Special Fire Fighting Procedures:	Use self contained breathing apparatus with full facepiece in pressure demand or other positive pressure mode. A straight water stream would spread fires.			
Unusual Fire & Explosion Hazards	A vapor accumulation would flash or explode if ignited.			

SECTION V REACTIVITY DATA				
Stability	Stable	Conditions to Avoid	Containers may burst at elevated temperature. Do not store in aluminum vessels. Avoid other ignition sources.	
Materials to Avoid	Avoid strong oxidizing agents.			
Hazardous Decomposition of Byproducts	Normal oxidation forms carbon dioxide and water vapor. Incomplete oxidation can produce carbon monoxide.			
Hazardous Polymerization	Will not occur			

SECTION VI HEALTH HAZARD DATA	
Acute Health	May cause eye, nose, respiratory track and skin irritation. Headache, dizziness, drowsiness and nausea are also symptoms of overexposure. High concentrations may cause narcosis.
Chronic Health	Long term exposure may lead to dermatitis.
Inhalation	Respiratory tract irritation.
Eye Contact	May cause eye irritation.
Skin Absorption	Skin irritation.
Skin Irritation	May cause skin irritation.
Ingestion	May cause headache, dizziness, drowsiness, nausea and narcosis.
First Aid	Move exposed person to fresh air. If breathing stops give artificial respiration. If unconscious, give oxygen. Get medical attention ASAP. For eye contact wash eyes with large amounts of water for 15 minutes. Get medical attention if eye irritation persists. Wash all skin exposed to product with soap and water. Remove contaminated clothing and dry before reuse. Get medical attention if irritation persists. INDUCE VOMITING give 2 glasses of water to drink and stick finger down throat. Send to hospital immediately.
Carcinogen	NO, this product is not found on the Federal OSHA, NTP, IARC, or Cal OSHA List.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE	
Precautions if Spilled	Remove all possible ignition sources. Ventilate area of spill or leak. For small quantities, absorb on paper towels, evaporate in safe place. Large quantities can be collected and atomized in combustion chamber. Product should not be allowed to enter sewer
Waste Disposal	due to explosion hazard. Empty containers can have residues, gases and mists are subject to proper waste disposal. Dispose of all wastes in accordance with Federal, State and local regulations.
Handling/Storage	Keep away from all ignition sources. Store in cool area.

SECTION VIII CONTROL MEASURES	
Respiratory Protection	For concentrations above 400 ppm, use a NIOSH approved organic vapor respirator.
Eye Protection	Safety goggles of glasses should be used.
Protective Gloves	Repeated skin contact can be avoided by wearing solvent resistant gloves.
Ventilation	Use adequate ventilation to keep vapor of mist concentrations below 400 ppm.

**COMPLIANT CAR CARE - MATERIAL SAFETY DATA SHEET
SUPER VISION GLASS CLEANER**